JVC

Color mini dome Camera

TK-T2101R



New **L**O**L**UX[™] line with True Day/Night and built-in IR LED mini dome Camera

Powerful economy line with LoLux quality

- 1/3" high resolution IT CCD and newly-developed 10-bit DSP
- High resolution camera with horizontal resolution 600TVL
- f = 2.8 10.5mm vari-focal length lens included
- Lolux sensitivity 0.05 Lux colour, 0.015 B/W, 0 lux with IR-LED
- Easy Wide-D for backlight compensation
- HLC Automatic High Light Compensation for extreme white light
- Built- in motion detection and max 8 areas of privacy mask
- Ultra compact design
- 24VAC/12VDC power supply

NEW PRODUCT NEWS

Specifications

		TK-T2101RU	TK-T2101RE
Camera and lens	Video system	NTSC	PAL
	Image device	1/3" High resolution IT CCD	
	Effective pixels	976 (H) × 494 (V)	976 (H) × 582 (V)
	Sync system	Internal / Linelock	
	Horizontal resolution	600 TVL	
	Focal length	f=2.8mm to 10.5mm	
	View angle	Horizontal: 101.8 (wide) to 27.4 (tele) degrees Vertical: 73.7 (wide) to 20.6 (tele) degrees	
	Video S/N ratio	50 dB	
	Minimum Illumination <b&w mode=""></b&w>	0.05 lx (F1.4, 50%) < 0.015 lx (F1.2, 50%), 0 lx (with IR LED ON) >	
	Day/Night	True Day/Night with IR cutoff filter	
	White Balance	ATW / Manual / Uer / Push / Push lock	
	AGC	OFF / ON	
	Shutter speed	1/60 to 1/10,000	1/50 to 1/10,000
	BLC	OFF / BLC / HLC	
	Digital noise reduction	Yes	
	Motion detect	Yes (4 areas)	
	Privacy Mask	Yes (max 8 areas)	
	IR LED	Super power LED 14 pcs,	
	IR wavelength	850 nm	
	IR distance	15M / 49ft	
	On-screen menu	Yes (English, French, German, Spanish, Russia, Porituguese, Simplified Chinese, Japanese)	
General	Power supply	24VAC / 12VDC	
	Power consumption	Max. 7 W	
	Operating Temperature	-10 to 50 deg C. / 14 to 122 deg.F	
ဗိ	Dimensions(WxHxD)	Dia. 112 mm x 97 mm / Dia 4.41 inches x 3.82 inches	
	Weight	Approx.300 g (0.67 lb)	