

ProHD 7-in AC/DC PORTABLE MONITOR (HDMI, COMPOSITE)

DT-X71C



Introduction:

The DT-X71C is an affordable high quality monitor for field and studio applications where HDMI or composite video inputs are available. This 7-inch LCD monitor produces 1024 x 600 resolution, H/V:160/160 viewing angle and a 900:1 contrast ratio. It has front & rear dual TALLY lights accessed through an RJ-45 rear panel connector, video flip, customer editable video title, and safety mark display. The monitor accepts 1 HDMI and 1 Composite video, 1 stereo audio input. The DT-X71C is powered via a 4-pin XLR 12V DC connector or a snap-on JVC BN-VF823 7.2V battery (optional).

Features:

- ◆ 1024×600 RGB
- ◆ 16:9 / 4:3 adjustable
- ◆ HDMI, Composite video, Stereo audio inputs
- ◆ Dual 3-color TALLY light
- ◆ Underscan / Overscan switch
- ◆ Canon DLSR scale zoom-in
- ◆ Picture flip
- ◆ Customer editable video TITLE

Package includes:



Ball Head



Sun hood



4-pin XLR AC-DC adapter



LCD Protector

ProHD

Specifications:

| SLCD Performance |                      |
|------------------|----------------------|
| Size             | 7.0 inches           |
| Resolution       | 1024×600 RGB         |
| Aspect ratio     | 16:9/4:3             |
| Color system     | NTSC/PAL             |
| Brightness       | 400cd/m2             |
| Contrast         | 900:1                |
| Color            | 16.77 million colors |
| Viewing angle    | H/V:160/160          |

| Input and Output |        |                              |
|------------------|--------|------------------------------|
| Input            | 1 BNC  | 1 Composite in               |
|                  | 1 HDMI | 1 HDMI in                    |
|                  | 2 RCA  | Stereo audio (L,R) in        |
| Output           | 1 BNC  | 1 Composite loop through out |

| Video Format |  |
|--------------|--|
| HDMI         | 480i / 576i / 480P / 576P                              |
|              | 1080i (60 / 59.94 / 50)                                |
|              | 720p (60 / 59.94 / 50)                                 |
|              | 1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98) |
| Composite    | PAL/NTSC   |

| General             |                            |
|---------------------|----------------------------|
| Working voltage     | DC12V, or Battery 6.5V-17V |
| Power consumption   | ≤ 6W                       |
| Working temperature | 0 °C ~ +40 °C              |
| Working humidity    | 10% ~ 90%                  |
| Storage temperature | -15 °C ~ +60 °C            |
| Storage humidity    | 10% ~ 90%                  |
| Dimensions          | 192×139×47mm               |
| Net weight          | 550g                       |

Distributed & supported by:



\* manufactured by SWIT. All Information in this document is subject to change without notice.